

MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI and Canadian WHMIS Standards

1. PRODUCT IDENTIFICATION

CHEMICAL NAME; CLASS: CARBON DIOXIDE

SYNONYMS: Carbon Anhydride, Carbonic Acid Gas, Carbonic Anhydride, Carbon Dioxide USP

CHEMICAL FAMILY NAME: Acid Anhydride

FORMULA: CO₂

Document Number: 50008

Note: This Material Safety Data Sheet is for Carbon Dioxide supplied in cylinders with 33 cubic feet (935 liters) or less gas capacity (DOT - 39 cylinders). For Carbon Dioxide in large cylinders refer to Document Number 10039.

PRODUCT USE:	Calibration of Monitoring and Research Equipment
SUPPLIER/MANUFACTURER'S NAME:	CALGAZ, LLC
ADDRESS:	821 Chesapeake Drive Cambridge, MD 21613
EMERGENCY PHONE:	CHEMTREC: 1-800-424-9300
BUSINESS PHONE:	1-410-228-6400
	General MSDS Information: 1-713/868-0440
	Fax on Demand: 1-800/231-1366

2. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	mole %	EXPOSURE LIMITS IN AIR					
			ACGIH-TLV		OSHA-PEL		NIOSH IDLH ppm	OTHER ppm
			TWA ppm	STEL ppm	TWA ppm	STEL ppm		
Carbon Dioxide	124-38-9	> 99.5%	5000	30,000	5000 10,000 (Vacated 1989 PEL)	30,000 (Vacated 1989 PEL)	40,000	NIOSH RELs: TWA = 5000 STEL = 30,000 DFG MAKs: TWA = 5000 PEAK = 2*MAK, 60 min., momentary value
Maximum Impurities		< 0.5%	None of the trace impurities in this product contribute significantly to the hazards associated with the product. All hazard information pertinent to this product has been provided in this Material Safety Data Sheet, per the requirements of the OSHA Hazard Communication Standard (29 CFR 1910.1200) and State equivalents standards.					

NE = Not Established.

See Section 16 for Definitions of Terms Used.

NOTE (1): ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-1998 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

3. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: Carbon Dioxide is a colorless, odorless, non-flammable gas. Over-exposure to Carbon Dioxide can increase respiration and heart rate, possibly resulting in circulatory insufficiency, which may lead to coma and death. At concentrations between 2-10%, Carbon Dioxide can cause nausea, dizziness, headache, mental confusion, increased blood pressure and respiratory rate. Exposure to Carbon Dioxide can also cause asphyxiation, through displacement of oxygen. If the gas concentration reaches 10% or more, suffocation can occur within minutes. Moisture in the air could lead to the formation of carbonic acid which can be irritating to the eyes.

SYMPTOMS OF OVER-EXPOSURE BY ROUTE OF EXPOSURE: The most significant routes of over-exposure for this gas are by inhalation, and contact with the cryogenic liquid.

INHALATION: Due to the small size of an individual cylinder of this product, no unusual health effects from exposure to the product are anticipated under routine circumstances of use. If this product is released in a small, poorly ventilated area (i.e. an enclosed or confined space), and if the concentration of Carbon Dioxide reaches 10% or more, suffocation can occur within minutes. At concentrations between 2-10%, Carbon Dioxide can cause nausea, dizziness, headache, mental confusion, increased blood pressure and respiratory rate. Carbon dioxide is an asphyxiant. Carbon Dioxide initially stimulates respiration and then causes respiratory depression. High concentrations result in narcosis. Symptoms in humans are as follows:

CARBON DIOXIDE CONCENTRATION

CONCENTRATION	OBSERVED EFFECT
1%	Slight increase in breathing rate.
2%	Breathing rate increases to 50% above normal level. Prolonged exposure can cause headache, tiredness.
3%	Breathing increases to twice normal rate and becomes labored. Weak narcotic effect. Impaired hearing, headache, increase in blood pressure and pulse rate.
4-5%	Breathing increases to approximately four times normal rate, symptoms of intoxication become evident and slight choking may be felt.
5-10%	Characteristic sharp odor noticeable. Very labored breathing, headache, visual impairment and ringing in the ears. Judgment may be impaired, followed within minutes by loss of consciousness.
50-100%	Unconsciousness occurs more rapidly above 10% level. Prolonged exposure to high concentrations may eventually result in death from asphyxiation.

High concentrations of this gas can also cause an oxygen-deficient environment. However, the asphyxiating properties of Carbon Dioxide will be reached before oxygen-deficiency is a factor.

CONTACT WITH SKIN or EYES: High concentrations of this gas in air may cause eye irritation with symptoms such as pain, redness, and tearing. Prolonged contact of high concentrations with the eyes can cause damage to the retinal ganglion cells.

HEALTH EFFECTS OR RISKS FROM EXPOSURE: An Explanation in Lay Terms. Over-exposure to Carbon Dioxide may cause the following health effects:

ACUTE: Due to the small size of the individual cylinder of this product, no unusual health effects from exposure to the product are anticipated under routine circumstances of use. The most significant hazard associated with this gas that Carbon Dioxide is an asphyxiant. Inhalation of Carbon Dioxide can cause nausea, dizziness, headache, mental confusion, increased blood pressure and respiratory rate. High concentrations of the gas in air may cause eye irritation. Contact with the eyes can cause damage to the retinal ganglion cells.

CHRONIC: There are currently no known adverse health effects associated with chronic exposure to this gas.

TARGET ORGANS: ACUTE: Respiratory system, CNS system and eyes. CHRONIC: None known.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH HAZARD (BLUE) 0

FLAMMABILITY HAZARD (RED) 0

PHYSICAL HAZARD (YELLOW) 0

PROTECTIVE EQUIPMENT

EYES RESPIRATORY HANDS BODY

See Section 8

For Routine Industrial Use and Handling Applications

4. FIRST-AID MEASURES

RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO THIS PRODUCT WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus equipment should be worn. Victim(s) who experience any adverse effect after over-exposure to this product must be taken for medical attention. Rescuers should be taken for medical attention, if necessary. Take copy of label and MSDS to physician or other health professional with victim(s).

No unusual health effects are anticipated after exposure to this product, due to the small cylinder size. If any adverse symptom develops after over-exposure to this product, remove victim(s) to fresh air, as quickly as possible. Trained personnel should cardio-pulmonary resuscitation, if necessary. Supplemental oxygen is not normally appropriate.

EYE EXPOSURE: If irritation of the eye develops after exposure to liquid or gas, open victim's eyes while under gentle running water. Use sufficient force to open eyelids. Have victim "roll" eyes. Minimum flushing is for 15 minutes. Seek medical assistance immediately, preferably an ophthalmologist.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing respiratory conditions may be aggravated by over-exposure to this product. Persons with chronic obstructive pulmonary disease can retain carbon dioxide abnormally. If oxygen is administered to such persons, raising the oxygen concentration in the blood depresses the breathing rate and raises the retained carbon dioxide levels in the blood to a dangerous level in these persons.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and reduce over-exposure.

5. FIRE-FIGHTING MEASURES

FLASH POINT: Not applicable.

AUTOIGNITION TEMPERATURE: Not applicable.

FLAMMABLE LIMITS (in air by volume, %):

Lower (LEL): Not applicable.

Upper (UEL): Not applicable.


FIRE EXTINGUISHING MATERIALS: Carbon Dioxide is commonly used as an extinguishing agent, and therefore, should not present a problem when trying to control a blaze. Use extinguishing media appropriate for surrounding fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Carbon Dioxide does not burn; however, containers, when involved in fire, may rupture or burst in the heat of the fire. Dusts of various reactive metals (e.g.: magnesium, zircon, titanium alloys), are readily ignited and explode in the presence of Carbon Dioxide. In the presence of moisture, cesium oxide ignites on contact with Carbon Dioxide. Metal acetylides or hydrides will also ignite or explode. Pressure in a container can build-up due to heat and it may rupture if pressure relief devices should fail to function.

Explosion Sensitivity to Mechanical Impact: Not Sensitive.

Explosion Sensitivity to Static Discharge: Not Sensitive.

SPECIAL FIRE-FIGHTING PROCEDURES: Structural fire-fighters must wear Self-Contained Breathing Apparatus and full protective equipment.



6. ACCIDENTAL RELEASE MEASURES

LEAK RESPONSE: Due to the small size of the cylinder, an accidental release of this product presents significantly less risk than a similar release from a larger cylinder. However, as with any chemical release, extreme caution must be used during emergency response procedures. In the event of a release in which the atmosphere is unknown, and in which other chemicals are potentially involved, evacuate immediate area. Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel. Locate and seal the source of the leaking gas. Allow the gas, to dissipate. Monitor the surrounding area for Carbon Dioxide and oxygen levels. The level of Carbon Dioxide must be below 3%, and the atmosphere must have at least 19.5 percent oxygen before personnel can be allowed in the area without Self-Contained Breathing Apparatus.

7. HANDLING and USE

WORK PRACTICES AND HYGIENE PRACTICES: Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this product could occur without any significant warning symptoms.

STORAGE AND HANDLING PRACTICES: Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature approximately 21°C, 70°F. Cylinders should be stored in dry, well-ventilated areas away from sources of heat, ignition and direct sunlight. Protect cylinders against physical damage. Isolate from other non compatible chemicals (refer to Section 10, Stability and Reactivity). Consider installation of leak detection and alarm for storage and use areas. Have appropriate extinguishing equipment in the storage area (i.e. sprinkler system, portable fire extinguishers). Use a check valve in the discharge line to prevent hazardous backflow. Never tamper with cylinders.

Full and empty cylinders should be segregated. Use a first-in, first-out inventory system to prevent full containers from being stored for long periods of time. These cylinders are not refillable. **WARNING!** Do not refill DOT 39 cylinders. To do so may cause personal injury or property damage.

SPECIAL PRECAUTIONS FOR HANDLING GAS CYLINDERS: **WARNING!** Compressed gases can present significantly safety hazards. During cylinder use, use equipment designed for these specific cylinders. Ensure all lines and equipment are rated for proper service pressure.

PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Follow practices indicated in Section 6 (Accidental Release Measures). Make certain application equipment is locked and tagged-out safely. Purge gas handling equipment with inert gas (i.e. nitrogen) before attempting repairs. Always use product in areas where adequate ventilation is provided.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation. Local exhaust ventilation is preferred, because it prevents dispersion of this gas into the work place by eliminating it at its source. If appropriate, install automatic monitoring equipment to detect the levels of Carbon Dioxide and of oxygen.

RESPIRATORY PROTECTION: Maintain Carbon Dioxide level below 3% and oxygen levels above 19.5% in the workplace. Use supplied air respiratory protection if Oxygen levels are below 19.5%, or unknown, during emergency response to a release of this product. If respiratory protection is needed, use only protection authorized in the U.S. Federal OSHA Standard (29 CFR 1910.134), applicable U.S. State regulations, or the Canadian CSA Standard Z94.4-93 and applicable standards of Canadian Provinces. Oxygen levels below 19.16.33% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998). The following NIOSH respiratory protection equipment guidelines for Carbon Dioxide in air are provided for additional information.

CARBON DIOXIDE CONCENTRATION

Up to 40,000 ppm:

Emergency or Planned Entry into Unknown Concentrations or IDLH Conditions: Any SCBA that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode, or any SAR that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary SCBA operated in pressure-demand or other positive-pressure mode.

Escape:

Any appropriate escape-type, SCBA.

EYE PROTECTION: Safety glasses. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

HAND PROTECTION: No special protection is needed under normal circumstances of use. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

BODY PROTECTION: No special protection is needed under normal circumstances of use. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

9. PHYSICAL and CHEMICAL PROPERTIES

GAS DENSITY @ 70°F (21.1°C) and 1 atm: 0.1144 lb/ft³ (1.833 kg/m³)
BOILING POINT: -78.5°C (-109.3°F)
FREEZING/MELTING POINT: (sublimation temperature) -78.5°C (-109.3°F)
SPECIFIC GRAVITY (air = 1) @ 70°F (21.1°C): 1.522
SOLUBILITY IN WATER vol/vol 68°F (20°C) and 1 atm: 0.90
EVAPORATION RATE (nBuAc = 1): Not applicable.
ODOR THRESHOLD: Not applicable.
VAPOR PRESSURE @ 70°F (21.1°C) (psig): 838 psig (5778 kPa)
COEFFICIENT WATER/OIL DISTRIBUTION: Not applicable.
APPEARANCE, ODOR AND COLOR: This product is a colorless, odorless gas.
HOW TO DETECT THIS SUBSTANCE (warning properties): There are no unusual warning properties associated with a release of this product.

10. STABILITY and REACTIVITY

STABILITY: Stable under conditions of normal temperature and pressure.
DECOMPOSITION PRODUCTS: None.
MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Carbon Dioxide will ignite and explode when heated with powdered aluminum, beryllium, cerium alloys, chromium, magnesium-aluminum alloys, manganese, thorium, titanium, and zirconium. In the presence of moisture, Carbon Dioxide will ignite with cesium oxide. Metal acetylides will also ignite and explode on contact with Carbon Dioxide.
HAZARDOUS POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID: Avoid exposing cylinders of Carbon Dioxide to extremely high temperatures, which could cause the cylinders to rupture or burst.

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA: Carbon Dioxide gas is an asphyxiant gas, which has physiological effects at high concentrations.

LCLo (Inhalation-Human) 9 pph/5 minutes	TCLo (Inhalation-Rat) 6 pph/24 hours: female	TCLo (Inhalation-Mouse) 55 pph/4 hours: male
LCLo (Inhalation-Mammal-species unspecified) 9000 ppm/5 minutes	10 day(s) after conception: Reproductive: Effects on Newborn: growth statistics (e.g.%, reduced weight gain)	6 day(s) pre-mating: Reproductive: Fertility: male fertility index (e.g. # males impregnating females per # males exposed to fertile non-pregnant females)
TCLo (Inhalation-Rat) 10000 ppm/24 hours/days-continuous: Blood: other changes	TCLo (Inhalation-Rabbit) 13 pph/4 hours: female 9-12 day(s) after conception: Reproductive: Specific Developmental Abnormalities: musculoskeletal system	TCLo (Inhalation-Mouse) 2 pph/8 hours: female 10 day(s) after conception: Reproductive: Fertility: post-implantation mortality (e.g. dead and/or resorbed implants per total number of implants); Specific Developmental Abnormaliti
TCLo (Inhalation-Rat) 6 pph/24 hours: female 10 day(s) after conception: Reproductive: Specific Developmental Abnormalities: musculoskeletal system, cardiovascular (circulatory) system, respiratory system	TCLo (Inhalation-Mouse) 55 pph/2 hours: male 3 day(s) pre-mating: Reproductive: Paternal Effects: spermatogenesis (incl. genetic material, sperm morphology, motility, and count)	
TCLo (Inhalation-Rabbit) 27,000 ppm/24 hours/30 days-continuous: Behavioral: somnolence (general depressed activity)		

SUSPECTED CANCER AGENT: Carbon Dioxide is not found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC, and therefore is not considered to be, nor suspected to be a cancer-causing agent by these agencies.

IRRITANCY OF PRODUCT: Contact with rapidly expanding gases can cause frostbite and damage to exposed skin and eyes.

SENSITIZATION OF PRODUCT: Carbon Dioxide is not a sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: Listed below is information concerning the effects of Carbon Dioxide on the human reproductive system

Mutagenicity: Carbon Dioxide has not been reported to cause mutagenic effects in humans.

Embryotoxicity: Carbon Dioxide has not been reported to cause embryotoxic effects in humans.

Teratogenicity: Carbon Dioxide has not been reported to cause teratogenic effects in humans. Clinical studies involving test animals exposed to high concentrations of Carbon Dioxide indicate teratogenic effects.

Reproductive Toxicity: Carbon Dioxide has not been reported to cause adverse reproductive effects in humans. Clinical studies involving test animals exposed to high concentrations of Carbon Dioxide indicate reproductive effects.

*A **mutagen** is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generation lines. An **embryotoxin** is a chemical which causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A **teratogen** is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A **reproductive toxin** is any substance which interferes in any way with the reproductive process.*

BIOLOGICAL EXPOSURE INDICES (BEIs): Currently, Biological Exposure Indices (BEIs) have not been determined for Carbon Dioxide.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL STABILITY: The gas will be dissipated rapidly in well-ventilated areas.

EFFECT OF MATERIAL ON PLANTS or ANIMALS: Due to the small cylinder size, no adverse effect on animals or plants is anticipated if one cylinder of this product is released.

EFFECT OF CHEMICAL ON AQUATIC LIFE: No evidence is currently available on the effects of this gas on aquatic life.

13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations and those of Canada and its Provinces. Return cylinders with any residual product to Air Liquide. Do not dispose of locally. For emergency disposal, secure the cylinder and slowly discharge the gas to the atmosphere in a well-ventilated area or outdoors, away from all sources of ignition.

14. TRANSPORTATION INFORMATION

THIS GAS IS HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Carbon dioxide
HAZARD CLASS NUMBER and DESCRIPTION: 2.2 (Non-Flammable Gas)
UN IDENTIFICATION NUMBER: UN 1013
PACKING GROUP: Not applicable.
DOT LABEL(S) REQUIRED: Class 2.2 (Non-Flammable Gas)

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2000): 120

MARINE POLLUTANT: Carbon Dioxide is not classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B).

SPECIAL SHIPPING INFORMATION: Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards. If transporting these cylinders in vehicles, ensure these cylinders are not exposed to extremely high temperatures (as may occur in an enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated during transportation.

NOTE: DOT 39 Cylinders ship in a strong outer carton (overpack). Pertinent shipping information goes on the outside of the overpack. DOT 39 Cylinders do not have transportation information on the cylinder itself.

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This gas is considered as Dangerous Goods, per regulations of Transport Canada.

PROPER SHIPPING NAME: Carbon dioxide
HAZARD CLASS NUMBER and DESCRIPTION: 2.2 (Non-Flammable Gas)
UN IDENTIFICATION NUMBER: UN 1013
PACKING GROUP: Not Applicable
HAZARD LABEL: Class 2.2 (Non-Flammable Gas)
SPECIAL PROVISIONS: None
EXPLOSIVE LIMIT AND LIMITED QUANTITY INDEX: 0.12
ERAP INDEX: None
PASSENGER CARRYING SHIP INDEX: None
PASSENGER CARRYING ROAD VEHICLE OR PASSENGER CARRYING RAILWAY VEHICLE INDEX: 75
NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2000): 120

14. TRANSPORTATION INFORMATION (Continued)

NOTE: Shipment of compressed gas cylinders via Public Passenger Road Vehicle is a violation of Canadian law (Transport Canada Transportation of Dangerous Goods Act, 1992).

15. REGULATORY INFORMATION

ADDITIONAL U.S. REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: This gas is not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows:

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this gas. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. TSCA INVENTORY STATUS: Carbon Dioxide is listed on the TSCA Inventory.

U.S. CERCLA REPORTABLE QUANTITIES (RQ): Not applicable.

U.S. STATE REGULATORY INFORMATION: Carbon Dioxide is covered under the following specific State regulations:

Alaska - Designated Toxic and Hazardous

Substances: Carbon Dioxide.

California - Permissible Exposure Limits for

Chemical Contaminants: Carbon Dioxide.

Florida - Substance List: Carbon Dioxide.

Illinois - Toxic Substance List: Carbon

Dioxide.

Kansas - Section 302/313 List: No.

Massachusetts - Substance List: Carbon

Dioxide.

Michigan - Critical Materials Register: No.

Minnesota - List of Hazardous Substances:

Carbon Dioxide

Missouri - Employer Information/Toxic

Substance List: Carbon Dioxide.

New Jersey - Right to Know Hazardous

Substance List: Carbon Dioxide.

North Dakota - List of Hazardous Chemicals,

Reportable Quantities: No.

Pennsylvania - Hazardous Substance List:

Carbon Dioxide.

Rhode Island - Hazardous Substance List:

Carbon Dioxide.

Texas - Hazardous Substance List: No.

West Virginia - Hazardous Substance List:

Carbon Dioxide.

Wisconsin - Toxic and Hazardous

Substances: Carbon Dioxide.

OTHER U.S. FEDERAL REGULATIONS:

- Generally recognized as safe (GRAS) as a direct human food ingredient when used as a leavening agent, processing aid, propellant, aerating agent and gas.
- Carbon Dioxide USP is regulated by the FDA as a prescription drug.
- Depending on specific operations involving the use of this product, the regulations of the Process Safety Management of Highly Hazardous Chemicals may be applicable (29 CFR 1910.119). Under this regulation Carbon Dioxide is not listed in Appendix A.
- Carbon Dioxide does not contain any Class I or Class II ozone depleting chemicals (40 CFR part 82).
- Carbon Dioxide is not listed as a Regulated Substance, per 40 CFR, Part 68, of the Risk Management for Chemical Release Prevention.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): Carbon Dioxide is not on the California Proposition 65 lists.

ADDITIONAL CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: Carbon Dioxide on the Canadian DSL Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: Argon is not on the CEPA Priorities Substances List.

CANADIAN WHMIS CLASSIFICATION: Carbon Dioxide is categorized as a Controlled Product, Hazard Class A, as per the Controlled Product Regulations.

16. OTHER INFORMATION

MIXTURES: When two or more gases or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

INFORMATION ABOUT DOT-39 NRC (Non-Refillable Cylinder) PRODUCTS

DOT 39 cylinders ship as hazardous materials when full. Once the cylinders are relieved of pressure (empty) they are not considered hazardous material or waste. Residual gas in this type of cylinder is not an issue because toxic gas mixtures are prohibited. Calibration gas mixtures typically packaged in these cylinders are Nonflammable n.o.s., UN 1956. A small percentage of calibration gases packaged in DOT 39 cylinders are flammable gas mixtures.

For disposal of used DOT-39 cylinders, it is acceptable to place them in a landfill if local laws permit. Their disposal is no different than that employed with other DOT containers such as spray paint cans, household aerosols, or disposable cylinders of propane (for camping, torch etc.). When feasible, we recommended recycling for scrap metal content. CALGAZ, LLC will do this for any customer that wishes to return cylinders to us prepaid. All that is required is a phone call to make arrangements so we may anticipate arrival. Scrapping cylinders involves some preparation before the metal dealer may accept them. We perform this operation as a service to valued customers who want to participate.


Further information about Carbon Dioxide can be found in the following pamphlets published by: Compressed Gas Association Inc. (CGA), 1725 Jefferson Davis Highway, Suite 1004, Arlington, VA 22202-4102. Telephone: (703) 412-0900

G-6	"Carbon Dioxide"
G-6.1	"Standard for Low Pressure Carbon Dioxide Systems at Customer Sites"
G-6.2	"Commodity Specification for Carbon Dioxide"
G-6.3	"Carbon Dioxide Cylinder Filling and Handling Procedures"
P-1	"Safe Handling of Compressed Gases in Containers"
P-2.6	"Standard Density Data, Atmospheric Gases and Hydrogen"
P-14	"Accident Prevention in Oxygen-Rich and Oxygen Deficient Atmospheres"
SB-2	"Oxygen Deficient Atmospheres"
AV-1	"Safe Handling and Storage of Compressed Gases"
AV-7	"Characteristics and Safe Handling of Carbon Dioxide"
	"Handbook of Compressed Gases"

PREPARED BY:

CHEMICAL SAFETY ASSOCIATES, Inc.
PO Box 3519, La Mesa, CA 91944-3519
619/670-0609

Fax on Demand: 1-800/231-1366



This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of CALGAZ, LLC knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.